NORTH CAROLINA ASSOCIATION OF RESCUE & EMERGENCY MEDICAL SERVICES, INC.

P.O. BOX 1914, GOLDSBORO, N.C. 27533-1914 TELEPHONE: 919/736-0506 FAX: 919/736-7759

E-MAIL: ncarems@ncarems.org

STATEMENT OF ELIGIBILITY

HEAVY RESCUE

*** PLEASE PRINT OR TYPE				
NAME OF DEPARTMENT				DATE
MAILING ADDRESS				
CITY	STATE	ZIP	COUNTY	
DEPARTMENT EMAIL ADDRESS				
COMM CENTER PHONE #()	BUSINESS PHONE	E #()		
DEPARTMENT CELL PHONE #()		FAX #		
CAPTAIN/CHIEF	EMAIL ADDRES	S		
WORK PHONE # ()	HOME PHONE # ()		CELL # () _	
SECRETARY	EMAIL ADDRE	SS		
WORK PHONE # ()	HOME PHONE # ()		CELL # () _	
DOES YOUR SQUAD PROVIDE?				
RESCUE ONLYEMS ONLYEMS	S/FIREEMS/RESCUE_	EMS/FIRE/F	RESCUE FI	RE/RESCUE

DOCUMENTS NEEDED TO CERTIFY & MUST ACCOMPANY THIS STATEMENT OF ELIGIBILITY:

1) COPY OF STATE CHARTER

2) AUTHORITY TO OPERATE WITH CITY/COUNTY

1 Revised: 01/01/24

AUTHORITY TO OPERATE

TO BE SIGNED & NOTARIZED BY CITY OR COUNTY OFFICIAL

THIS IS TO CERTIFY THAT		
	Name of Department	
	PERATING IN IZED TO PROVIDE <u>HEAVY RESCUE</u> IN TH	
	PRINT NAME	SIGNED
COUNTY OR CITY OFFICIAL		
		TITLE
(NOTARY SEAL)		
COUNTY OF	STZ	ATE OF
	20, APPEARED BEFORE ME T INSTRUMENT, AND HE(OR SHE) DULY ACKNOWLED HEREIN CONTAINED WERE TRUE TO THE BEST OF	
MY COMMISSION EXPIRES:		NOTARY PUBLIC
TO BE SIGNED & NOTARIZED B	Y DEPARTMENT OFFICIAL	
THIS IS TO CERTIFY THAT		
	Name of Department	
	PERATING IN IZED TO PROVIDE <u>HEAVY RESCUE</u> IN TH	
COUNTY.		
	PRINT NAME	SIGNED
DEPARTMENT OFFICIAL		
		TITLE
(NOTARY SEAL)		
COUNTY OF	ST	ATE OF
DESCRIBED HEREIN AND WHO EXECUTED THE	20, APPEARED FOREGOING INSTRUMENT, AND HE (OR SHE) DUL ATEMENTS THEREIN CONTAINED WERE TRUE TO T	Y ACKNOWLEDGED TO ME THAT HE (OR
MY COMMISSION EXPIRES:		NOTARY PUBLIC

BOTH SIGNATURES ARE REQUIRED

Heavy Rescue: Inspectors Initials 2 Revised: 01/01/24

MINIMUM STANDARD REQUIREMENTS - NCAR&EMS

HEAVY RESCUE

HEAVY RESCUE IS DEFINED AS ADVANCED LEVELS OF ALL RESCUE, ADVANCED EXTRICATION, AND BASIC LIFE SUPPORT FUNCTIONS AS AN INITIAL RESPONDER WITH MINIMUM ADVANCED EQUIPMENT.

1. MINIMUM PERSONNEL / ORGANIZATION REQUIREMENTS:

(ENTER NUMBER OF PERSONNEL WITH EACH CERTIFICATION) FIRST RESPONDER - ____ MEDICAL RESPONDER - ___ EMT - ___ EMT-I - ___ EMT-P - ___ RESCUE CERTIFIED - ___ RN/MICN - ___

NUMBER OF PERSONNEL WITH CERTIFICATION

A MINIMUM OF EIGHT (8) PERSONNEL SHALL HOLD RESCUE CERTIFICATIONS
AS ERT, RT-VMR & RT-ROPES OR TR-VMR & TR-ROPES OR TECHNICAL
RESCUER & TR-VR & TR MACHINERY & AGRICULTURE

2. TYPE OF RESCUE TO PERFORM:

AS SPECIFIED BY THE CONTRACT WITH THE AHJ

3. VEHICLE:

VEHICLE(S) USED FOR HEAVY RESCUE SHALL BE CAPABLE OF TRANSPORTING RESCUE PERSONNEL AND EQUIPMENT TO AN INCIDENT SAFELY AND CANNOT EXCEED THE VEHICLE'S TOTAL GVWR, INCLUDING THE CHASSIS, BODY, AND RESCUE EQUIPMENT AND MEDICAL CARE EQUIPMENT WHEN LOADED. ALL EQUIPMENT SHALL BE LOADED ON APPARATUS AND RESPONSE READY.

Heavy Rescue: Inspectors Initials 3 Revised: 01/01/24

4.	MINIMUM REQUIRED EQUIPMENT: DEPT. NAME
	AR&EMS, INC., PRESENTATIVEDATE:
AP	PROVED:YESNO INSPECTOR'S SIGNATURE:
	YOU MUST HAVE EACH OF THE FOLLOWING ITEMS TO MEET ELIGIBILITY REQUIREMENTS FOR CERTIFICATION.
A.	COMMUNICATIONS EQUIPMENT
	1 - MOBILE RADIO PER VEHICLE 8 - PORTABLE RADIOS
	L COMMUNICATIONS EQUIPMENT SHALL HAVE THE CAPABILITY TO COMMUNICATE BETWEEN EMERGENCY ENCIES OF THE LOCAL JURISDICTION.
в.	GENERATOR
	1 GENERATOR, 5KW, MINIMUM, MOBILE 1 GENERATOR, 8KW, MINIMUM, MOBILE
c.	LIGHTING EQUIPMENT
	8 HANDLIGHTS, PORTABLE, BATTERY POWER OR RECHARGEABLE HANDLIGHTS. ADEQUATE SCENE LIGHTS TO ILLUMINATE THE SCENE PER THE AHJ. MAY BE PORTABLE, TRIPOL MOUNTED, LIGHT TOWER OR OTHER TYPE LIGHTS. FLASHLIGHTS WILL NOT BE INCLUDED IN THESE LIGHTS. (THESE LIGHTS MAY BE QUARTZ, FLOURESCENT, LED, ETC.) 200 FT. TOTAL OF 12/3 EXT. CORDS, MAY BE DIFFERENT LENGTHS 2 - 12/3 GFCI
D.	FIRE PROTECTION EQUIPMENT
	1 EXTINGUISHER, PORTABLE, 10 LB., ABC TYPE 1 EXTINGUISHER, PORTABLE, 10 LB., CO 2 TYPE
E.	PROTECTIVE CLOTHING: (MINIMUM OF EIGHT (8) SETS)
	8 PAIR GLOVES, LEATHER PALM 8 PAIR GOGGLES/SAFETY GLASSES 8 PROTECTIVE COATS, PROTECTIVE COVERALLS FLAME RESIST. IE.EX. 6.0-7.5 NOMEX 8 PROTECTIVE PANTS, PROTECTIVE COVERALLS FLAME RESIST. IE. EX. 6.0-7.5 NOMEX 8 PAIR PROTECTIVE FOOTWEAR 8 SAFETY RATED HELMET 8 HEARING PROTECTION
F.	CRIBBING AND STABILIZATION
	60 BLOCKS, 4"X4"X24" (MINIMUM), PREFERRED SOUTHERN YELLOW PINE OR DOUGLAS FIR 20 BLOCKS, 2"X4"X24" (MINIMUM), PREFERRED SOUTHERN YELLOW PINE OR DOUGLAS FIR 12 BLOCKS, 6"X6"X24" (MINIMUM), PREFERRED SOUTHERN YELLOW PINE OR DOUGLAS FIR 12 PAIR WEDGES, 6"X6"X24" (MINIMUM), PREFERRED SOUTHERN YELLOW PINE OR DOUGLAS FIF 20 PAIR WEDGES, 4"X4"X18" (MINIMUM), PREFERRED SOUTHERN YELLOW PINE OR DOUGLAS FIF 2 PER VEHICLE WHEEL CHOCKS - (Note: Not Required on Department Ambulances) 8 STEP CRIBBING 16 PICKETS 1"X48" MINIMUM, ROLLED STEEL OR # 8 REBAR EQUIVALENTS 16 EACH PICKETS CAPS/COVERS

1	,200 FT - GENERAL USE LIFE SAFETY ROPE AS SPECIFIED IN NFPA 2500. THIS MAY BE CUT
	TO DIFFERENT LENGTHS. (NOTE - AGENCIES WILL BE REQUIRED TO MAINTAIN
	MANUFACTURER'S DOCUMENTATION TO DEMONSTRATE COMPLIANCE WITH THE ABOVE
	REQUIREMENTS DURING AN INSPECION, UNLESS YOU HAVE BEEN SUCCESSFULLY
	INSPECTED BY A PREVIOUS NCAREMS STANDARD AND RETAINED THAT EQUIPMENT).
	ACCORDINGLY, THE NFPA GENERAL USE LIFE SAFETY ROPES ARE TO BE 11 mm to 16 mm
	·
	IN DIAMETER WITH A MBS OF 40 KN.
	4 HARNESSES, CLASS II TYPE
	4 HARNESSES, CLASS III TYPE (MAY BE A CLASS II W/CHEST HITCH ATTACHED)
3	36 CARABINERS, LOCKING GATE, MUST MEET NFPA 2500 GENERAL USE REQUIREMENTS
	(ALUMINUM UST BE STAMPED). HARDWARE MUST BE SPECIFICALLY SIZED FOR THE SIZE OF
	ROPE BEING USED. THESE UPDATES ARE NOT REQUIRED IF YOU HAVE BEEN SUCCESSFULLY
	INSPECTED BY A PREVIOUS NCAREMS STANDARD AND RETAINED THAT EQUIPMENT.
1	14 DESCENDERS, MAY BE ANY COMBINATION OF APPROVED GENERAL USE DESCENDERS WITH A
	MINUMUM OF ONE (1) BRAKE BAR RACK. (8'S MUST BE WINGED TYPE)
1	1 RIGGING PLATE
	4 - 7mm - 9mm PRUSSIK SLINGS, LENGTHS MAY VARY PER THE AHJ'S NEEDS. All SOFTWARE
	MUST MEET NFPA 2500 GENERAL USE REQUIREMENTS, UNLESS YOU HAVE BEEN
	SUCCESSFULLY INSPECTED BY A PREVIOUS NCAREMS STANDARD AND HAVE RETAINED THAT
	EQUIPMENT. (Note: EYE TO EYE OR SOWN SLINGS MAY BE SUBSTITUTED FOR THE ABOVE
	BUT MUST MEET THE REQUIREMENTS of NFPA 2500 GENERAL USE AND BE CORRECTLY
_	SIZED FOR THE SIZE OF ROPE BEING USED)
	3 25 FT X 1/2 IN., BODY CORD, KERNMANTLE
	3 25 FT X 1 IN., WEBBING - THIS IS IN ADDITION TO THE NFPA COLORS BELOW TUBULAR
	IS RECOMMENDED)
	6 5 FT X 1 IN. TUBULAR WEBBING - GREEN
	6 12 FT X 1 IN. TUBULAR WEBBING - YELLOW
	6 15 FT X 1 IN. TUBULAR WEBBING - BLUE
	6 20 FT X 1 IN. TUBULAR WEBBING - RED
	6 25 FT X 1 IN. TUBULAR WEBBING - BLACK
	2 BASKET STRETCHER, STOKES TYPE - WITH ADJUSTABLE BRIDLE (PREMADE OR MFG)
4	4 DOUBLE SHEAVE PULLEYS, 1/2 IN. X 2 IN. MINIMUM DIAMETER & RATED FOR GENERAL USE
	OR 2 PERSON LOADS, MAY BE STEEL, ALUMINUM, ETC. PER THE AHJ
8	3 SINGLE SHEAVE PULLEYS, 1/2 IN. X 2 IN. MINIMUM DIAMETER & RATED FOR GENERAL USE
	OR 2 PERSON LOADS
2	2 1/2 IN. SINGLE SHEAVE PULLEY PRUSSIK MINDING RATED FOR GENERAL USE OR 2 PERSON
	LOADS
6	6 EDGE ROLLERS/PADS
1	1 CINCH COLLAR
H. HAND	DLED TOOLS
•	2 HAMMER, 4 LB., SLEDGE TYPE, 15 IN. HANDLE
	2 HAMMER, 22 OZ. CLAW - TYPE W/15 IN. HANDLE
	O SHOWEL MILITARY TYPE FOLDING
	1 BOLD CUTTERS 24 IN
	L DOLL COLLEGO, 24 IN.
	L DOLL CULLERO, 30 IN.
	2 FLAT TIME MKI BAK 2 DDV DAD 15 TW
	2 SHOVEL, MILITARY TYPE, FOLDING L BOLT CUTTERS, 24 IN. L BOLT CUTTERS, 36 IN. 2 FLAT TYPE PRY BAR 2 PRY BAR, 15 IN. 3 PRY BAR, 51 IN.
	O PRI DAK, DI IN.
	L 36 IN, CROWBAR
	HALIGAN/HOOLIGAN BAR, 36 IN. HANDLE
1	1 PICKS - POINT & CHISEL 36" HANDLE
1	1 10 FT. PIKE POLE
2	1 36 IN. CROWBAR 1 HALIGAN/HOOLIGAN BAR, 36 IN. HANDLE 1 PICKS - POINT & CHISEL 36" HANDLE 1 10 FT. PIKE POLE 2 HATCHET (Note: A Pry Axe may be substituted for a hatchet)
	1 6 LB. FLAT HEAD AXE
1	1 6 LB. PICK HEAD AXE

G. HIGH LEVEL EQUIPMENT

		8 LB. SLEDGEHAMMER
		LONG HANDLE, ROUND POINT SHOVEL
	2	LONG HANDLE, SQUARE SHOVEL
I.	CUTT	ING TOOLS
	2	RIGID FRAME HACKSAWS
	— ₁	2 ASSORTED HACK SAW BLADES
	‡	Z ASSONIED HACK SAW BEADES UNNDCAM CARDENIED MYDE RIDDING
	‡	HANDSAW, CARPENTER TYPE, RIPPING
	;	BOW SAW - 24 IN.
		CHAIN SAW, GASOLINE OR ELECTRIC, OR HYDRAULIC SPARE CHAIN
	1	SPARE CHAIN
	+	PAIR CHAINSAW CHAPS
	4	RECIPROCATING SAWS @ LEAST TWO MUST BE ELECTRIC (AC CORDED) BATTERY POWERED
		TOOLS MUST HAVE 1 SPARE BATTERY PER TOOL
		4 ASSORTED RECIPROCATING SAWBLADES
	1	ROTARY SAW 14", W/SPARE BLADES FOR METAL & MASONARY
	1	CIRCULAR SAW 7 1/4", W/6 SPARE BLADES
	2	BOTTLES OF SPRAY LUBRICANT (NON-FLAMMABLE)
	1	AIR CHISEL - W/ASSORTED BITS, REGULATOR & HOSES
	1	CIRCULAR SAW 7 1/4", W/6 SPARE BLADES BOTTLES OF SPRAY LUBRICANT (NON-FLAMMABLE) AIR CHISEL - W/ASSORTED BITS, REGULATOR & HOSES IMPACT HAMMER, W/1 - BULLPOINT, 1 - CHISEL AND 1 - SPADE, GAUGES, HOSES and REGULATORS. (ACCEPTABLE TOOLS MAY INCLUDE EITHER THE PARATECH PAKHAMMER TYPE OF
		REGULATORS. (ACCEPTABLE TOOLS MAY INCLUDE EITHER THE PARATECH PAKHAMMER TYPE OF
		AJAX X11 - RK AXESS)
J.	TRAF	FIC AND CROWD CONTROL AND HAZ-MAT EQUIPMENT
		TRAFFIC CONES OR REFLECTIVE TRIANGLES
		BARRIER TAPE, 2000 FT.
	8	TRAFFIC VEST, REFLECTIVE TYPE (MUST BE DOT COMPLIANT PER AHJ)
	1	INCIDENT COMMAND VEST KIT
	2	FLASHLIGHTS, WITH TRAFFIC WAND, RED, YELLOW OR ORANGE
	1	PAIR OF BINOCULARS PER RESCUE VEHICLE, 7 X 50 mm POWER
	1	D.O.T. EMERGENCY RESPONSE GUIDEBOOK PER RESCUE VEHICLE - CURRENT EDITION
	1	MULTI-GAS METER (TO INCLUDE 02, LEL & CO)
ĸ.	PULL	ING EQUIPMENT
		WINCH 8000 LB. CAP, TRUCK MOUNTED
		SINGLE SHEAVE SNATCH BLOCKS FOR WINCH
	2	HANDWINCH, (COME-A-LONG TYPE), 2 TON AND MAY BE CHAIN OR CABLE. WEBBING TYPE
		NOT ACCEPTED).
	4	CHAIN, 3/8 X 6 FT., GRADE 70 TRANSPORT CHAIN-W/CLEVIS HOOKS
	4	CHAIN, 3/8 X 12 FT., GRADE 70 TRANSPORT CHAIN-W/CLEVIS HOOKS
	1	CHAIN, 3/8 X 20 FT., GRADE 70 TRANSPORT CHAIN-W/CLEVIS HOOKS
	8	CHAIN SHORTENERS, 3/8 IN., GRADE 70 TRANSPORT CHAIN-W/CLEVIS HOOKS
	1	PORT-A-POWER, 4 TON, RESCUE KIT
	2	48 IN. HIGH LIFT JACKS
		60 IN. HIGH LIFT JACKS
	<u>-</u>	CHAIN SHORTENERS, 3/8 IN., GRADE 70 TRANSPORT CHAIN-W/CLEVIS HOOKS PORT-A-POWER, 4 TON, RESCUE KIT 48 IN. HIGH LIFT JACKS 60 IN. HIGH LIFT JACKS BOTTLE JACK, HYDRAULIC, 10 TON BOTTLE JACK, HYDRAULIC, 20 TON HIGH PRESSURE AIRBAG SET, 200 TON CAPACITY-W/ACCESSORIES-HOSES, REGULATORS &
	⁻	BOTTLE JACK, HYDRAULIC, 20 TON
	₁	HIGH PRESSURE AIRBAG SET, 200 TON CAPACITY-W/ACCESSORIES-HOSES, REGULATORS &
		GAUGES
L.	HEAV	Y HYDRAULIC RESCUE TOOLS
	1	HADDAILL IC CODEADED
		HYDRAULIC SPREADER
	—— Ť	HYDRAULIC CUTTER
		HYDRAULIC RAMS
	1	HYDRAULIC CUTTER HYDRAULIC RAMS POWER UNIT
	+	BACK-UP POWER UNIT
		ote: Battery operated hydraulic rescue tools may be used in substation of other
		imilar type power tools. If using battery operated hydraulic rescue tools you
	m	ust have 1 Spare Battery Per Tool.

М.	HAN	D TOOLS - MECHANICS TOOLS (MANUAL & POWER)
		6 SCREWDRIVERS, STRAIGHT BLADE, ASSORTED SIZES AT LEAST 2 MUST BE 15 IN.
		4 SCREWDRIVERS, PHILLIPS BLADE, ASSORTED SIZES
		A CENTERRINGU CRRING I CARER
		1 WRENCH, CRESCENT TYPE, 10 IN 1 PIPEWRENCH, 18 IN 1 KNIFE, UTILITY TYPE, HOOKED BLADE 1 HAMMER, 2 LB., MACHINIST TYPE
		1 PIPEWRENCH, 18 IN
		1 KNIFE, UTILITY TYPE, HOOKED BLADE
		1 HAMMER, 2 LB., MACHINIST TYPE
		1 PLIERS, VISE GRIP TYPE, 6 IN.
		1 PLIERS, VISE GRIP TYPE, 10 IN.
		1 PLIERS, SLIP JOINT TYPE, 9 1/2 IN.
		1 PLIERS, SLIP JOINT TYPE, 16 IN CHANNEL LOCK TYPE
		1 COLD CHISEL, 1/2 IN. X 12 IN.
		1 COLD CHISEL, 1 IN. X 12 IN. 1 PAIR 8 IN. TIN SNIPS 1 DRILL - HAMMER TYPE 3/4 IN., W/ASSORTED BITS 1 IMPACT WRENCH 1/2 IN. DRIVE - MAY BE PNEUMATIC - (IF PNEUMATIC MUST HAVE
		1 PAIR 8 IN. TIN SNIPS
		1 DRILL - HAMMER TYPE 3/4 IN., W/ASSORTED BITS
		1 IMPACT WRENCH 1/2 IN. DRIVE - MAY BE PNEUMATIC - (IF PNEUMATIC MUST HAVE
		HOSES, GAUGES, REGULATOR AND ACCESSORIES. IF BATTERY MUST HAVE 1 SPARE BATTERY PER TOOL
		1 SOCKET SET, 1/4 IN. DRIVE, STANDARD (3/16 THRU 1/2) AND METRIC (4 THRU 13 MM)
		1 SOCKET SET, 3/8 IN. DRIVE, STANDARD (7/16 THRU 13/16) AND METRIC (8 THRU 19 MM)
		1 SOCKET SET, 1/2 IN. DRIVE, STANDARD (7/16 THRU 1") AND METRIC (9 THRU 22 MM)
		1 IMPACT SOCKET SET 1/2 IN. DRIVE, STANDARD (7/16 THRU 1") AND METRIC (9 THRU 22
		MM)
		1 SOCKET SET - 3/4 IN. DRIVE, STANDARD, 7/8 IN. THRU 2 3/8 IN. 1 COMBINATION WRENCH SET, STANDARD & METRIC SETS- STANDARD-1/4 IN. THRU 1 5/8
		1 COMBINATION WRENCH SET, STANDARD & METRIC SETS- STANDARD-1/4 IN. THRU 1 5/8
		IN., METRIC, 6 mm THRU 32 mm
		1 HEX KEY WRENCH SET STANDARD & METRIC 5/64, 3/8 & 1.5 mm THRU 10 mm 1 TORX DRIVERS SET, SOCKET TYPE, SIZES 15 THRU 45
		2 ROLL OF ELECTRIC TAPE
		2 ROLL OF DUCT TAPE
		CELLANEOUS
		1 SET OF PRINTED INCIDENT COMMAND FORMS PER AHJ: Download these forms at the
		following link which: http://www.ncarems.org/standards.php
		1 SET OF DEPARTMENTAL SOG'S - ONSITE
		1 COUNTY MAP PER VEHICLE
		1 N.C. STATE MAP PER VEHICLE
		2 FIRE RETARDANT BLANKETS
		4 TARPS, 10 FT. X 12 FT. (MINIMUM SIZE)
		2 TARPS, 18 FT. X 20 FT
		1 GLOBAL POSITIONING SYSTEM (GPS) (NOTE: GPS MUST BE ABLE TO ACCEPT COORDINATES
		FOR LANDING ZONES, SEARCHES & MAY NOT BE A VEHICLE TYPE NOR A CELL PHONE)
		1 SET OF TOPOGRAPHICAL MAPS SET TO COVER LOCAL REGION (ELECTRONIC OR PAPER VERSIONS ACCEPTED)
_		1 OSHA COMPLIANT SAFETY FUEL CAN
		1 LANDING ZONE LIGHT KIT (CAN BE MANUFACTURED OR CUSTOM MADE BY AHJ. IF YOUR AHJ
		USES VEHICLES OR OTHER MEANS FOR LZ SETUP, PLEASE SPECIFY YOUR PLAN TO THE INSPECTOR)
ο.	LAD	DERS
		1 IADDED EVMENOTON MVDE 24 EM IENOMU NEDA ETDE GERVICE DAMED
		1 LADDER, EXTENSION TYPE, 24 FT. LENGTH, NFPA FIRE SERVICE RATED
		2 LADDERS, 12 FT. NFPA FIRE SERVICE RATED 1 LADDER, ATTIC TYPE, 10 FT. LENGTH MINIMUM, NFPA FIRE SERVICE RATED
		I HADDER, ATTIC TIPE, TO PT. HENGIN MINIMUM, NEFA PIRE SERVICE RATED

P.	WATE	TER RESCUE EQUIPMENT:			
	8 8 3	PFD, TYPE III/V, VEST TYPE, U.S. COAST GUARD APPROVED - (NOTE: THE STANDARDS COMMITTEE RECOMMENDS THAT IF AN ORGANIZATION IS PLANNING TO BECOME CERTIFIED AT THE SWIFTWATER LEVEL THE ORGANIZATION PURCHASE THE TYPE V, RATHER THAN THE TYPE III VESTS TO REDUCE EXPENSE LATER) WATER RESCUE HELMETS WATER RESCUE THROW BAGS (A FLOATING ROPE AS DEFINED by NFPA 1006,2021 EDITION AND IS OF SUFFICIENT DIAMETER TO BE GRIPPED BY BARE WET HANDS),3/8 IN. X 70 FT 00 FT OF WATER RESCUE ROPE W/STORAGE BAG, (A FLOATING ROPE AS DEFINED by NFPA 006, 2021 EDITION AND IS OF SUFFICIENT DIAMETER TO BE GRIPPED BY BARE WET HANDS) 18 IN. TYPE IV THROWABLE DEVICE			
Q.	SCBA	UNITS			
 R.	4	SELF CONTAINED BREATHING APPARATUS MINIMUM 30 MINUTE DURATION EACH WITH A P.A.S.S. (Personal Alert Safety System) Device ALARM SPARE AIR CYLINDERS (COMPATIBLE TO FIT ABOVE MENTIONED SCBA) CAL CARE - ALL MEDICAL EQUIPMENT TO BE N.C.O.E.M.S. APPROVED			
	1 3 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	LONG SPINE BOARD, WITH STRAPS PER AHJ EXTRICATION DEVICE (K.E.D. TYPE) EXTRICATION COLLARS, 2 ADULT & 1 PEDIATRIC OXYGEN CYLINDERS OXYGEN REGULATORS, 0-15 LPM NON REBREATHING MASKS, INFANT, CHILD AND ADULT NASAL CANNUALS - ADULT, CHILD AND INFANT BAG-VALVE MASK, WITH HIGH CONCENTRATION KIT FOR ADULT, CHILD & INFANT SUCTION DEVICE, PORTABLE SUCTION UNIT W/RIGID TIP OR SOFT TIP SUCTION CATHETER BLANKET SPLINT KIT, ASSORTED TO INCLUDE TRACTION SPLINTS TRAUMA KIT - PER MEDICAL RESPONDER STANDARDS CRITERIA			
	1 3 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	EXTRICATION DEVICE (K.E.D. TYPE) EXTRICATION COLLARS, 2 ADULT & 1 PEDIATRIC OXYGEN CYLINDERS OXYGEN REGULATORS, 0-15 LPM NON REBREATHING MASKS, INFANT, CHILD AND ADULT NASAL CANNUALS - ADULT, CHILD AND INFANT BAG-VALVE MASK, WITH HIGH CONCENTRATION KIT FOR ADULT, CHILD & INFANT SUCTION DEVICE, PORTABLE SUCTION UNIT W/RIGID TIP OR SOFT TIP SUCTION CATHETER BLANKET SPLINT KIT, ASSORTED TO INCLUDE TRACTION SPLINTS			

NOTE: IF AGENCY HAS A NCOEMS PERMITTED AMBULANCE, THE ABOVE MEDICAL CARE EQUIPMENT WILL BE AUTOMATICALLY CREDITED DURING THE INSPECTION.