NORTH CAROLINA ASSOCIATION OF RESCUE & EMERGENCY MEDICAL SERVICES, INC.

P.O. BOX 1914, GOLDSBORO, N.C. 27533-1914 TELEPHONE: 919/736-0506 FAX: 919/736-7759

E-MAIL: ncarems@ncarems.org

STATEMENT OF ELIGIBILITY

CONFINED SPACE RESCUE

*** PLEASE PRINT OR TYPE						
NAME OF DEPARTMENT	DATE					
MAILING ADDRESSST	. ADDRESS					
CITYSTATE	ZIPCOUNTY					
DEPARTMENT EMAIL ADDRESS						
COMM CENTER PHONE #()BUSINESS PHONE #()						
DEPARTMENT CELL PHONE #()	FAX #					
CAPTAIN/CHIEFEMAIL ADD	RESS					
WORK PHONE #() HOME PHONE #()	CELL #()					
SECRETARYEMAIL ADD	RESS					
WORK PHONE #()HOME PHONE #()	CELL #()					
DOES YOUR SQUAD PROVIDE?						
RESCUE ONLYEMS ONLYEMS/FIREEMS/RESCUE _	EMS/FIRE/RESCUE FIRE/RESCUE					
DOCUMENTS NEEDED TO CERTIFY	& MUST ACCOMPANY THIS					

STATEMENT OF ELIGIBILITY:

<u>1) COPY OF STATE CHARTER</u> 2) AUTHORITY TO OPERATE WITH CITY/COUNTY

AUTHORITY TO OPERATE

TO BE SIGNED & NOTARIZED BY CITY OR COUNTY OFFICIAL

THIS IS TO CERTIFY THAT	
Name of Department	
IS AN ACTIVE OPERATING SERVICE, OPERATING IN	CITY
OR COUNTY AND IS HEREBY AUTHORIZED TO PROVIDE <u>CONFINED SPACE RESCUE</u> IN THE ABOVE MENTIONED CITY OR COUNTY.	
PRINT NAME	SIGNED
COUNTY OR CITY OFFICIAL	0101125
	TITLE
(NOTARY SEAL)	
COUNTY OFSTATE OF	
ON THEDAY OF20, APPEARED BEFORE ME THE SAID INDIVIDUAL DES HEREIN AND WHO EXECUTED THE FOREGOING INSTRUMENT, AND HE (OR SHE) DULY ACKNOWLEDGED TO ME THAT HE (OR EXECUTED SAME AND THAT THE STATEMENT THEREIN CONTAINED WERE TRUE TO THE BEST OF HIS (OR HER) KNOWLEDG BELIEF.	
MY COMMISSION EXPIRES:NOTARY	PUBLIC
TO BE SIGNED & NOTARIZED BY DEPARTMENT OFFICIAL	
THIS IS TO CERTIFY THAT	
Name of Department	
IS AN ACTIVE OPERATING SERVICE, OPERATING IN	CITY
OR COUNTY AND IS HEREBY AUTHORIZED TO PROVIDE <u>CONFINED SPACE RESCUE</u> IN THE ABOVE MENTIONED CITY OR COUNTY.	
PRINT NAME	SIGNED
DEPARTMENT OFFICIAL	
TITLE	
(NOTARY SEAL)	
COUNTY OF STATE OF	
ON THE DAY OF 20, APPEARED BEFORE ME THE SAID IN DESCRIBED HEREIN AND WHO EXECUTED THE FOREGOING INSTRUMENT, AND HE (OR SHE) DULY ACKNOWLEDGED TO ME T SHE) EXECUTED THE SAME AND THAT THE STATEMENTS THEREIN CONTAINED WERE TRUE TO THE BEST OF HIS (OR HER AND BELIEF.	
MY COMMISSION EXPIRES:NOTAR	Y PUBLIC
Confined Space Rescue Inspectors Initials Revised:	01/01/25

BOTH SIGNATURES ARE REQUIRED

MINIMUM STANDARD REQUIREMENTS - NCAR&EMS

CONFINED SPACE RESCUE

1. <u>MINIMUM PERSONNEL / ORGANIZATION REQUIREMENTS:</u>

NUMBER OF PERSONNEL WITH CERTIFICATION

(ENTER NUMBER OF PERSONNEL WITH EACH CERTIFICATION)

FIRST RESPONDER - MEDICAL RESPONDER - EMT -

EMT-I - ____ EMT-P - ____ RESCUE CERTIFIED - ____ RN/MICN - ____

A MINIMUM OF EIGHT (8) PERSONNEL SHALL HOLD RESCUE CERTIFICATIONS AS ERT, RT-VMR & RT-ROPES, *TR-GENERAL* & *TR-CONFINED SPACE* OR TECHNICAL RESCUER & TR-CONFINED SPACE.

Note if previously certified as ERT, RT-VMR & RT-ROPES you must also be certified as Confined Space Technician.

ORGANIZATIONS OPERATING AT THE CONFINED SPACE RESCUE TECHNICIAN LEVEL OF SERVICE SHALL HAVE A MINIMUM OF EIGHT (8) QUALIFIED PERSONNEL WHICH MEET ALL THE REQUIREMENTS OF THE OPERATIONS LEVEL PLUS THE REQUIREMENTS FOR THE TECHNICIAN LEVELS OF SERVICE AS PRESCRIBED BY NFPA 1670 AND OPERATING IN COMPLIANCE WITH 29 CFR 1910.146 & 1910.147.

> CONFINED SPACE RESCUE - N.C FIRE/RESCUE COMMISSION PROGRAMS OR OTHER RECOGNIZED COURSES OF INSTRUCTION MEETING NFPA 1670 TECHNICIAN LEVEL

2. TYPE OF RESCUE TO PERFORM:

AS SPECIFIED BY THE CONTRACT WITH THE AHJ

3. VEHICLE:

VEHICLE(S) USED FOR CONFINED RESCUE SHALL BE CAPABLE OF TRANSPORTING RESCUE PERSONNEL AND EQUIPMENT TO AN INCIDENT SAFELY AND CANNOT EXCEED THE VEHICLE'S TOTAL GVWR, INCLUDING THE CHASSIS, BODY, AND RESCUE EQUIPMENT AND MEDICAL CARE EQUIPMENT WHEN LOADED. ALL EQUIPMENT SHALL BE LOADED ON APPARATUS AND RESPONSE READY.

Confined Space Rescue Inspectors Initials

4. <u>MINIMUM REQUIRED EQUIPMENT:</u> DEPT. NAME_

NCAR&EMS, IN REPRESENTATI	•		DATE :	
APPROVED :	YES	NO	INSPECTOR'S SIGNATURE:	

YOU MUST HAVE EACH OF THE FOLLOWING ITEMS TO MEET ELIGIBILITY REOUIREMENTS FOR CERTIFICATION IN ADDITION TO THE LISTED EQUIPMENT FOR LIGHT RESCUE.

MINIMUM OF EIGHT (8) TEAM MEMBERS SHALL HAVE THE FOLLOWING:

____ KNIFE

CONFINED SPACE EQUIPMENT:

- 600 ft.-GENERAL USE LIFE SAFETY ROPE AS SPECCIFIED IN NFPA 2500. THIS MAY BE CUT TO DIFFERENT LENGTHS. (NOTE - AGENCIES WILL BE REQUIRED TO MAINTAIN MANUFACTURER'S DOCUMENTATION TO DEMONSTRATE COMPLIANCE WITH THE ABOVE REQUIREMENTS DURING AN INSPECION, UNLESS YOU HAVE BEEN SUCCESSFULLY INSPECTED BY A PREVIOUS NCAREMS STANDARD AND RETAINED THAT EQUIPMENT). ACCORDINGLY, THE NFPA GENERAL USE LIFE SAFETY ROPES ARE TO BE 11 mm to 16 mm IN DIAMETER WITH A MBS OF 40 KN.
- 24 CARABINERS LOCKING GATE, MUST MEET NFPA 2500 GENERAL USE REQUIREMENTS (ALUMINUM UST BE STAMPED). HARDWARE MUST BE SPECIFICALLY SIZED FOR THE SIZE OF ROPE BEING USED. THESE UPDATES ARE NOT REQUIRED IF YOU HAVE BEEN SUCCESSFULLY INSPECTED BY A PREVIOUS NCAREMS STANDARD AND RETAINED THAT EQUIPMENT.
- 18 7mm 9mm PRUSSIK SLINGS, LENGTHS MAY VARY PER THE AHJ'S NEEDS. All SOFTWARE MUST MEET NFPA 2500 GENERAL USE REQUIREMENTS, UNLESS YOU HAVE BEEN SUCCESSFULLY INSPECTED BY A PREVIOUS NCAREMS STANDARD AND HAVE RETAINED THAT EQUIPMENT. (Note: EYE TO EYE OR SOWN SLINGS MAY BE SUBSTITUTED FOR THE ABOVE BUT MUST MEET THE REQUIREMENTS of NFPA 2500 GENERAL USE AND BE CORRECTLY SIZED FOR THE SIZE OF ROPE BEING USED)
- 4 DESCENDERS, MAY BE ANY COMBINATION OF APPROVED GENERAL USE DESCENDERS WITH A MINUMUM OF ONE (1) BRAKE BAR RACK. (8'S MUST BE WINGED TYPE)
- 1 INTRINSICALLY SAFE FLASHLIGHT WITH EXTRA BATTERIES
- 8 INTRINSICALLY SAFE LIGHT SOURCES
- 1 INTRINSICALLY SAFE COMMUNICATIONS SYSTEM
- 1 INTRINSICALLY SAFE AIR MONITORING EQUIPMENT (to include 02, LEL, and CO)
- 1 EXPLOSION PROOF EXHAUST FANS WITH TRUNK HOSE
- 2 STRAIGHT LADDERS MINIMUM OF 12' (NFPA FIRE SERVICE RATE/OSHA APPROVED) ____ 1 AC HOTSTICK
- 6 CLASS III HARNESSES (MAY BE CONVERTED CLASS II WITH A CHEST HITCH)
- 1 MILLER BOARD/SKED STRETCHER/LITTER/LSP HALFBACK (Device can be of team's choice)
- 1 Pr. WRISTLETS (Manufactured or Pre-made)
- 1 TRIPOD (minimum of 8 feet tall)
- 1 HOISTING SYSTEM FOR TRIPOD MAY BE CONVENTIONAL OR MANUFACTURED
- 1 FALL ARREST DEVICE FOR TRIPOD MAY BE CONVENTIONAL OR MANUFACTURED
- 6 1 in. x 48 in., PICKETS MAY BE ROLLED STEEL OR #8 REBAR EQUVALENT W/CAPS
- 1 LOCKOUT TAGOUT KIT WITH MINIMUM OF 8 LOCKS
- 2 FLUOROCARBON HORNS
- **4 SPARE SCBA CYLINDERS**
- 2 DOUBLE SHEAVE PULLEYS, 2 IN. MINIMUM DIAMETER & RATED FOR GENERAL USE OR 2 PERSON LOADS, MAY BE STEEL, ALUMINUM, ETC
- 2 SINGLE SHEAVE PULLEYS, 2 IN. MINIMUM DIAMETER & RATED FOR GENERAL USE OR 2 PERSON LOADS MAY BE STEEL, ALUMINUM, ETC

Confined Space Rescue Inspectors Initials

Revised: 01/01/25

- ____ 2 <mark>2 IN. MINIMUM DIAMETER SINGLE SHEAVE PULLEY PRUSSIK MINDING RATED FOR GENERAL USE</mark> OR 2 PERSON LOADS
- 2 1/2 in. ASCENDERS 1 KNOT PASSING PULLEY
- 4 SUPPLIED AIR BREATHING APPARATUS WITH ESCAPE PACK, HOSES, MASKS & AIRLINES
- 1 SAR Air Supply Unit w/minimum 2 hour supply

 6 APPROVED CS BLANK ENTRY PERMITS PER AHJ

Confined Space Rescue Inspectors Initials